

PCT/IB04/00654

REC'D 10 MAY 2004

WIPO

PCT

PA 1147690

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 26, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.


APPLICATION NUMBER: 60/453,418

FILING DATE: March 10, 2003

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**



W. Montgomery
W. MONTGOMERY
Certifying Officer

BEST AVAILABLE COPY

60453418 . 031003

03/10/03

Jc950 U.S. PTO

Please type a plus sign (+) inside this box →



03-11-03

A/prou

PTO/SB/16 (8-00)

Approved for use through 10/31/2002. OMB 0651-0032
 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

INVENTOR(S)					
Given Name (first and middle (if any))	Family Name or Surname	Residence (City and either State or Foreign Country)			
Wilhelmina Johan Pieter	Jansen de Wet	Vanderbijlpark, South Africa Vanderbijlpark, South Africa			
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
Extraction of Oxygenates from a Hydrocarbon Stream					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number _____		<div style="border: 1px solid black; padding: 5px; text-align: center;"> Place Customer Number Bar Code Label here </div>			
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name		Browning Bushman P.C.			
Address		5718 Westhelmer			
Address		Suite 1800			
City		Houston		State	Texas
Country		U.S.A.		ZIP	77057-5771
		Telephone	713-266-5593	Fax	713-266-5169
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification		Number of Pages		<input type="checkbox"/> CD(s), Number	
		10			
<input checked="" type="checkbox"/> Drawing(s)		Number of Sheets		<input type="checkbox"/> Other (specify)	
		1			
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees				FILING FEE AMOUNT (\$)	
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number		02-4345		\$160.00	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME C. James Bushman, Attorney

TELEPHONE 713-266-5593

Date 03-10-03

REGISTRATION NO. 24,810

(if appropriate)

Docket Number:


Sasol S.A.-1

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OF COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C.

P18LARGE/REV05

60453418-031003

CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10)			Docket No.
Applicant(s): Wilhelmina Jansen and Johan Pieter de Wet			Sasol S.A.-1
Serial No. To Be Assigned	Filing Date Herewith	Examiner To Be Assigned	Group Art Unit To Be Assigned
Invention: Extraction of Oxygenates from a Hydrocarbon Stream			
<p>I hereby certify that this <u>Provisional Patent Application and all related documents</u> (Identify type of correspondence)</p> <p>is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to: The Commissioner of Patents and Trademarks, Washington, D.C.</p> <p>20231-0001 on <u>March 10, 2003</u> (Date)</p> <p><u>Sheri Cooper</u> (Typed or Printed Name of Person Mailing Correspondence)</p> <p><u></u> (Signature of Person Mailing Correspondence)</p> <p><u>EL010850280US</u> (Express Mail Mailing Label Number)</p>			
Note: Each paper must have its own certificate of mailing.			

-1-

EXTRACTION OF OXYGENATES FROM A HYDROCARBON STREAM

BACKGROUND OF THE INVENTION

This invention relates to a method for extracting oxygenates from a hydrocarbon stream.

Many methods for extracting oxygenates from hydrocarbon streams are known. Such extraction methods include hydrogenation, azeotropic distillation, extractive distillation, vapour phase dehydration, liquid phase dehydration and liquid-liquid extraction.

This invention relates to a process for extracting or separating oxygenates from the condensation product of a low temperature Fischer-Tropsch reaction, to produce a condensation product that is particularly suitable for the production of linear alkyl benzene.

SUMMARY OF THE INVENTION

According to the invention there is provided a method for extracting oxygenates from the condensation product of a low temperature Fischer-Tropsch reaction containing 15% to 30% by weight olefins, typically less than 25% by weight olefins, 60% to 80% by weight paraffins and 5% to 10% by weight oxygenates, while preserving the olefin content of the condensation product. The oxygenate extraction process being a liquid-liquid extraction process using dry methanol or a mixture of methanol and water, preferably a mixture of methanol and water, as the solvent.

-2-

The liquid-liquid extraction process preferably takes place in a liquid extraction column.

Preferably, a raffinate from the extraction column is sent to a stripper column from which a hydrocarbon feed stream containing olefins and paraffins and typically less than 0.01% by weight oxygenates exits as a bottoms product, and methanol exiting from the top of the stripper column is preferably recycled to the extraction column.

An extract from the extraction column is sent to a recovery column from which oxygenates and water exit as a bottoms product and methanol exits as a tops product, with the methanol from the tops product and water from the bottoms product preferably being recycled to the extraction column.

BRIEF DESCRIPTION OF THE DRAWING

The Figure is a block diagram of a process of the invention for extracting oxygenates from a hydrocarbon stream.

DESCRIPTION OF PREFERRED EMBODIMENTS

This invention relates to a process for extracting oxygenates from a hydrocarbon condensate stream from a low temperature Fischer-Tropsch reaction. The substantially oxygenate-free hydrocarbon stream can be used in the production of linear alkyl benzene.

In the Fischer-Tropsch process, synthesis gas (carbon monoxide and hydrogen) obtained either from the gasification of coal or the reforming of natural gas, is reacted over a Fischer Tropsch catalyst to produce a mixture of hydrocarbons ranging from methane to waxes and smaller amounts of oxygenates.

-3-

In a low temperature Fischer-Tropsch reaction, the reaction takes place in a slurry bed reactor or fixed bed reactor, preferably a slurry bed reactor, at a temperature in the range of 160°C - 280°C, preferably 210°C - 260°C, and a pressure in the range of 18-50 bar (gauge), preferably between 20-30 bar (gauge), in the presence of a catalyst. The catalyst may include iron, cobalt, nickel or ruthenium. However, a cobalt-based catalyst is preferred for the low temperature reaction. Usually, the cobalt catalyst is supported on an alumina support.

During the Fischer-Tropsch reaction, a lighter hydrocarbon vapour phase is separated from a liquid phase comprising heavier liquid hydrocarbon products. The heavier liquid hydrocarbon product (waxy products) is the major product of the reaction and may, for example, be hydrocracked to produce diesel and naphtha.

The lighter hydrocarbon vapour phase which comprises gaseous hydrocarbon products, unreacted synthesis gas and water is condensed to provide a "condensation product" which comprises an aqueous phase and a hydrocarbon condensation product phase.

The hydrocarbon condensation product includes olefins, paraffins in the C₄ to C₂₆ range, and oxygenates including alcohols, esters, aldehydes, ketones and acids.

Typically, a hydrocarbon condensation product for a low temperature Fischer-Tropsch reaction contains 15%-30% by weight olefins, 60%-80% by weight paraffins, and 5%-10% by weight oxygenates. It has, surprisingly, been found that even though this condensation product has a low olefin content, it can be used in the production of linear alkyl benzene. However, it is necessary to first extract the oxygenates as these species have a negative effect on the alkylation reaction. There is therefore a need to find a process for extracting oxygenates, but at the same time preserve the olefin concentration. For the production of linear alkyl benzene, the hydrocarbon condensate product is fractionated into a C₁₀ - C₁₃ cut which, by way of

-4-

example, contains 22% by weight olefins, 71% by weight paraffins and 7% by weight oxygenates. As mentioned above, the oxygenates need to be extracted to provide a product fit for production of linear alkyl benzene.

In the prior art, many methods of extracting oxygenates from hydrocarbon streams are suggested. Such removal methods include hydrogenation, azeotropic distillation, extractive distillation, vapour phase dehydration, liquid phase dehydration and liquid-liquid extraction. It has been found that liquid-liquid extraction is a preferred method of oxygenate extraction because, if the correct solvent is selected, the olefin concentration can be preserved. In liquid liquid extraction, the solvent can be any polar material that has partial miscibility with the feed stream 14, such as tri-ethanol amine, tri-ethylene glycol with between zero and 20% water, acetonitrile with between 5% and 20% water, acetol, diols, methanol, or ethanol and water. A combination of the above solvents is also possible. Normally, a high-boiling point solvent is preferred because the solvent recovery steps after extraction requires less energy than will be the case for a low-boiling point solvent. However, it has been found that dry methanol, or a mixture of methanol and water, which is a low-boiling point solvent, need not suffer from this drawback, because it can be effective at low solvent to feed ratios (this can be lower than 1:1 if the required oxygenate extraction is not too severe). Furthermore, one would not expect to be able to use methanol and water as a solvent in a liquid-liquid extraction column to extract oxygenates from the abovementioned hydrocarbon condensate because a study of the different azeotropes with water that exist in the hydrocarbon condensate would lead one to expect that it would not be possible to distil water in a solvent recovery column without azeotroping oxygenates overhead as well. Surprisingly, this turns out not to be the case.

With reference to the Figure, a liquid-liquid extraction process of the invention includes an extraction column 20. The the fractionated condensation product of a low temperature Fischer-Tropsch reaction described above 14 is fed into the extraction column 20 at, or near, the bottom thereof and a solvent stream 21 comprising methanol or a mixture

-5-

of methanol and water is fed into the extraction column 20 at or near the top thereof.

Raffinate 22 from the top of the extraction column 20, which includes olefins and paraffins and a small amount of solvent, enters a raffinate stripper column 23 and a hydrocarbon feed stream olefins, paraffins and less than 0.01% by weight oxygenates exits as a bottoms product 24, while solvent exits as a tops product 25 and is returned to the solvent feed stream 21. If it is desired to recover the bottoms product 24 as a vapour stream, this can be done by adding a vapour side draw to the column just above the reboiler. The liquid product from the reboiler will then be a very small effluent stream.

An extract 26 is drawn from the bottom of the extraction column 20 and is fed to solvent recovery column 27. Oxygenates exit as a bottoms product 28 from the solvent recovery column 27, while solvent exits as a tops product 29 and is recycled to the solvent stream 21. The oxygenate content of the tops product 29 can be as low as 50 ppm, depending on the solvent to feed ratio used in the extraction column 20.

As mentioned above, normally, a high-boiling solvent is preferred for liquid-liquid extraction because the solvent recovery steps after extraction requires less energy than will be the case for a low-boiling solvent. However, it has been found that dry methanol, or a mixture of methanol and water, which is a low-boiling solvent, need not suffer from this drawback, because it can be effective at low solvent to feed ratios (this can be lower than 1:1 if the required oxygenate extraction is not too severe).

A study of the different azeotropes that exist between components in the feed and water would lead one to expect that it would not be possible to distil water overhead in the solvent recovery column 27 without azeotropeing oxygenates overhead as well. Surprisingly, this turns out not to be the case. Methanol, which does not form azeotropes with any of the other species present, prevents the water/oxygenate azeotropes from distilling

-6-

over at the same temperature as the paraffins and olefins. This appears to be due to an extractive distillation effect. Additionally, it is possible to distil the paraffins and olefins overhead, while recovering all the oxygenates as bottom products (this is not possible for a dry methanol system, because only a fraction of the paraffins and olefins can be distilled overhead without carrying over oxygenates in a dry methanol system). This has the effect of enhancing the overall paraffin and olefin recovery of the process, because the overheads 29 of the solvent recovery column 27 is recirculated to the extraction column 20, which means that the paraffins and olefins will be forced to leave the process in the product stream 24.

It is therefore possible to have a pure hydrocarbon (paraffin and olefin) stream 24, and a pure oxygenate and water stream 28 as products from the process, without the use of a counter solvent in the extraction column. In this mode of operation, all the methanol, and part of the water (10-50%) are also recovered in the overhead stream 29.

Because the bottoms product 28 contains a high percentage of water (10-60%), this stream will form two liquid phases that can be decanted in a decanter 30. The organic phase will be a pure oxygenate stream 31, which leaves the process as a product. The aqueous phase will be stream 32, which can be recycled to the extraction column 20. This stream can either enter the extraction column at the top along with the solvent stream 21, or slightly lower down the column 20, to prevent the low amount of oxygenates that will be present in this stream from appearing in the raffinate stream 22.

It is also possible to run the extraction column 20 and the solvent recovery column 27 at different methanol / water ratios. This may be desirable because a high water content in the extraction column 20 will lead to increased solvent to feed ratios (because of reduced solubility of oxygenates in the solvent), while a certain amount of water is necessary to achieve the extractive distillation effect in combination with methanol to recover all the paraffins and olefins as overhead products in the solvent recovery column 27. The different methanol / water ratios in the two

-7-

columns (20 and 27) can be achieved by diverting some of the water in stream 32 to stream 26 by means of a stream 33.

After passing the $C_{10} - C_{13}$ hydrocarbon feed stream mentioned above through the abovementioned oxygenate extraction process using a mixture of methanol (95% by weight) and water (5% by weight) and a solvent to feed ratio of 1.2:1, the purified hydrocarbon feed stream contains 23% by weight olefins, 77% by weight paraffins and less than 0.01% by weight oxygenates. Not only does the extraction process extract oxygenates, it also preserves the olefin content of the hydrocarbon feed. The purified hydrocarbon feed stream containing olefins is particularly useful in the production of linear alkyl benzene.

EXAMPLE

The tables on the following pages set out a mass balance for a typical extraction process according to the invention. The results are by way of example only and do not limit the scope of the invention. The numbering system of the unit operations and flow streams correspond to the numbering system in the Figure.

Extraction column 20:

Stream	14		21		22		26	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100.00	3000	100.00	3000	100.00	2729	100.00	3270
Total $C_{10}-C_{13}$ olefins/paraffins	92.34	2770	0.000	0.000	96.99	2647	3.764	123.1
Total oxygenates	7.230	216.9	0.000	0.000	0.1477	4.033	6.509	212.8
Lights and Heavies	0.4087	12.26	0.000	0.000	0.4204	11.47	0.02394	0.783
Water	0.01127	0.338	5.000	150.0	0.0437	1.195	4.560	149.1
Methanol	0.000	0.000	95.00	2850	2.394	65.34	85.14	2784

In stream 14 the paraffin/olefin content is 69.34% by weight paraffins and 23% by weight olefins.

Raffinate Stripper column 23:

-8-

Stream	25		24	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100.00	65.60	100.00	2663
Total C10-C13 olefins/paraffins	3.647	2.393	99.29	2645
Total oxygenates	0.001524	0.001	0.1513	4.03
Lights and Heavies	0.07163	0.047	0.4291	11.43
Water	1.658	1.088	0.004016	0.107
Methanol	94.62	62.08	0.1226	3.267

In stream 24 the paraffin/olefin content is 74% to 77% by weight paraffins and 23% to 26% by weight olefins.

Solvent recovery column 27 :

Stream	29		28	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100.00	2945	100.00	324.8
Total C10-C13 olefins/paraffins	3.726	109.7	4.115	13.37
Total oxygenates	0.009981	0.294	65.44	212.6
Lights and Heavies	0.02664	0.785	0.000	0.000
Water	1.705	50.24	30.44	98.89
Methanol	94.53	2784	0.000	0.000

CLAIMS


1. A method for extracting oxygenates from the hydrocarbon condensation product of a low temperature Fischer-Tropsch reaction, while preserving the olefin content of the hydrocarbon condensation product, the method including the step of extracting the oxygenates in a liquid liquid extraction process using dry methanol or a mixture of methanol and water as the solvent.
2. The method according to claim 1, wherein, prior to extraction, the hydrocarbon condensation product contains 15% to 30% by weight olefins, 60% to 80% by weight paraffins and 5% to 10% by weight oxygenates.
3. The method according to claim 1, wherein the solvent is a mixture of methanol and water.
4. The method according to claim 1, wherein liquid-liquid extraction process takes place in a liquid extraction column.
5. The method according to claim 4, wherein a raffinate from the extraction column is sent to a stripper column from which a hydrocarbon feed stream containing olefins and paraffins and less than 0.01% by weight oxygenates exits as a bottoms product.
6. The method according to claim 5, wherein the tops product from the stripper comprises methanol which is recycled to the extraction column.
7. The method according to claim 4, wherein an extract from the extraction column is sent to a recovery column from which oxygenates and water exits as a bottoms product and methanol exits as a tops product, with the methanol from the tops product and

10 MAR '03 16:39 FROM

TO 0-0917132665169 P.14/15
604-53418 031003

-10-

water from the bottoms product being recycled to the extraction column.



This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**